

CALCULATOR ERRATA

PAGE	CHANGE
2	Figure 1 should show cartridge being removed, not inserted.
33	Line 8, delete SPACE BAR Line 9, delete = Line 11, change *.9=325 to CLX 325=.9*
35	In first Stack Display column, change the Y across from 20 SPACE BAR to X.
42	Under "Natural Logarithm Function," move 10 one line up.
43	Under the X Display, change 35.00 to 35 and 492.15656 to 492.15659
55	***Needs technical correction, both examples give the same results.
58	Move 4.3 SHIFT up one line
59	Under the X Display column, delete 11.267538 and move 10.851547 up one line. Line 6 should read: The X register should display -4.6723534
60	Delete Y 9.3956574 at bottom of page
63	In the second paragraph, change PVDRD to PVORD
66	At bottom of page, move asterisk (*) up one space. Change X on second line from bottom to Y.
68	Change 12 in Stack Display column to 12.00
69	In the first line in the first Stack Display, change 12.00 to 12 Change 9.2555 to 9.255 in both the first and second line of the second Stack Display Under Comments opposite 1.096968, add 2.688E + 43

PAGE	CHANGE
72	In the second Stack Display column, change 100000 to 100000.00
86	Old Contents column should read: 2)) STP etc.
95	In Old Contents the STP across from the first 0096 should be RETURN
97	Put a space between the lines 145 SPACE BAR and LIST SPACE BAR
98	Change last item in program from ON to STP
99	***Needs technical correction, the second program doesn't work.
101	At bottom of page, change DELETE TO DEL
102	Change program from line 0126 to 0167 as follows: 0126 PAUSE 0127 XLT 0128 3 0136 146 0144 RETURN 0145 STP 0146 85 0154 STO 0155 1 0163 POPC 0164 RETURN 0165 STP 0166 STP 0167 STP
115	***Needs technical correction, the program gives an incorrect result.

PAGE

CHANGE

156

Under the X Display, near the bottom of the page, change
53 to 3